
Description:	Synthetic esters combination with additives.
Aspect:	Light brown liquid.
Concentration:	47,5 – 52,0%.
pH (sol. 10%):	6,5 – 8,5
Charge:	Anionic
Light and heat fastness:	Good
Solubility:	Easily soluble in cold or hot water.
Electrolyte stability:	Chrome stable at normal retanning conditions.
Application:	Fatliquoring.
Properties:	<p>UP SOFT® SS is recommended to very soft leather and can be used alone or in combination with the UP SOFT® portfolio.</p> <p>If used during the neutralization, results in great penetration and high internal lubrication. The UP SOFT® SS has very good light and heat resistance, produces uniform dyes, does not loses the grain and has excellent compatibility with other anionic fatliquors.</p>
Use guideline:	<p>The dosage varies according the article:</p> <ul style="list-style-type: none">🔗 Upholstery: 16,0 – 20,0% over the shaved wet blue weight;🔗 Floater: 18,0 – 24,0% over the shaved wet blue weight;🔗 Napa: 4,0 – 6,0% over the shaved wet blue weight.
Storage:	<p>We recommend keeping the product sealed in the original package, in a clean and controlled environment, avoiding extreme temperatures.</p> <div style="text-align: center;"></div>
Package:	190 Kg metal drums.